



Dimensions	310mm x 310mm x 416mm (h)	12.2in x 12.2in x 16.38in (h)	
Weight	16,5 kg	36,4 lb	
Voltage-Frequency	230V - 50Hz	230V - 60Hz	115V - 60Hz
Current Consumption	1,7 A	3,5 A	
Compressor Power	1/6 HP		
Power Consumption (Cooling)	225 W	770 Btu\h	
Power Consumption (Heating)	400 W	1365 Btu\h	
Cooling Capacity *	450 W	1540 Btu\h	
Minimum Water Flow	400 l/h	105 Usgal\h	
Air Flow	155 m³\h	5475 CFH	
Maximum Exchanger's Pressure	0,6 bar	8,7 PSI	
Ambient Temperature Range	5°C - 38°C	32°F - 100°F	
Certification	CE		
Protection Grade	IPX4		

* the value reported refers to the following condition: room temperature 30°C (86°F), w ater temperature 25°C (77°F)

Material:	Drawing: TK 500 – technical data		
Thickness:	File: TK_500_technical_drawing		
Finishing:	Your code:	Code:	
Volume:	Tol.	Scale: 1: 5	Date: 24/10/2014
Approved:	Via A.Sansovino, 35 48124 RAVENNA – ITALY Tel. +39 0544 408333 Fax 280084 http://www.tecoonline.com		
	Drawer: Matteo		

AS BY LAW ENACTED WE RESERVE US THE PROPERTY OF THIS DOCUMENT WITH THE PROHIBITION OF REPRODUCE IT, SAVE IT INTO ARCHIVES SYSTEM, GIVE IT OR HOWEVER LENT IT TO THIRD PARTY WITHOUT OUR AUTHORIZATION. EVERY VIOLATION INVOLVES THE COMPENSATION FOR THE UNDERGONE DAMAGES.WE MAKE RESERVATIONS ABOUT ALL THE RIGHTS DERIVING FROM PATENTS OR MODELS.

Modify:

Drawer: